

## Green SCOB under-cabinet accent lighting

24V constant-voltage LED strip for dry indoor cabinetry. Select the colour and length before ordering.

7-YEAR WARRANTY

IP20 / DRY INDOORS

10mm PCB


10m MAX RUN

|                 |                              |
|-----------------|------------------------------|
| Supply          | 24V DC constant voltage      |
| LED technology  | SCOB LED Strip               |
| LEDs per metre  | 280                          |
| Power per metre | 9 W/m                        |
| Light output    | Approx. 1,157 lm/m           |
| CRI             | >95 for white-light versions |
| PCB width       | 10mm                         |
| Cutting         | 25mm (2.5cm)                 |
| Maximum run     | 10m                          |
| Lengths offered | 1m-10m                       |
| Protection      | IP20 - non-waterproof        |
| Backing         | 3M Tape                      |
| Warranty        | 7 years                      |



Product appearance shown for reference. The installation example below illustrates this fixed light colour.

## Green installation example




This fixed-colour green SCOB strip is shown installed beneath a kitchen cabinet. The scene illustrates this product colour only, not a colour-changing mode.

Illustrative scene; screens, surrounding light and surface finishes affect the perceived colour. Use a physical sample where colour matching is critical.

### Green under-cabinet lighting

Choose the length and any cut-to-measure option on the product page. Use only in dry indoor locations; follow the marked cut points and 10m run limit.

## Dimensions, description and handling



Use the dimension drawing for strip width and the permitted cutting arrangement. Confirm connector clearance separately; a 10mm strip does not guarantee every 10mm connector or profile fits.

## Colour, output and product identification

| Colour | Nominal lm/m  | Actual 1m SKU      |
|--------|---------------|--------------------|
| Green  | 1,157 approx. | SCOB24V-GRE-01M-UC |

The actual 1m SKUs above identify this cabinet range. Ordered lengths use the same colour prefix with -02M-UC through -10M-UC. The selected variant on the product page shows the full order SKU. A cut-to-measure request does not change the purchased variant SKU.

Approximate output is the merchant-confirmed SCOB figure across this range. CRI >95 for white-light versions.

## What to order

Choose the strip colour and purchased length, then enter the required cut length where offered. Check the order summary for cable and connector selections. A compatible 24V DC driver, dimmer and aluminium profile are separate unless explicitly included in your order.

View this product and its current options at [atomled.co.uk](https://atomled.co.uk)

## Installation, power and cautions

### 1. Plan and isolate

Measure the cabinet runs and cable routes. Disconnect the power before cutting, wiring or mounting. Keep IP20 strip in dry indoor locations away from splashes and steam.

### 2. Cut correctly

Cut only at the marked cut points at the interval on page 1. Make a clean square cut; do not cut through components. Confirm that your requested length follows the permitted interval.

### 3. Mount on a suitable surface

Use a suitable aluminium profile for heat dissipation and a clean, dry mounting surface. Press on the backing, not on the COB emitting layer. Do not crease, twist, pierce or overlap the strip.

### 4. Match the supply


Use a regulated 24V DC constant-voltage LED driver. Size it for total connected strip wattage plus the driver manufacturer's recommended headroom. Observe polarity and the ratings of every cable, connector and controller.

### 5. Test and finish

Test the strip uncoiled before final fixing. With power isolated, secure the connections and protect exposed contacts from shorts. Verify operation, colour and dimming before fitting the diffuser.

## Typical wiring

### Skydance V1-L - single-colour dimming example



### Use a 24V DC constant-voltage supply for this strip.

Without dimming, connect the strip directly to the 24V driver, matching + and -.

Source: Skydance V1-L manufacturer instructions


**WARNING:** Never connect this 24V DC strip directly to 220-240V AC mains. Incorrect voltage can damage the light. Mains connections must be made by a competent installer in accordance with applicable electrical requirements.

Do not exceed the stated maximum continuous run. Longer or branched installations need suitably designed feeds; do not simply daisy-chain beyond the limit. Keep drivers ventilated and accessible.


Damage caused by incorrect voltage or direct mains connection is not covered by warranty where ATOM LED is not at fault. ATOM LED Lighting Ltd accepts no liability for loss or damage caused by such connection where it is not at fault. This does not exclude liability for our negligence or breach of statutory duty, or affect your statutory rights.

## See the colour in your kitchen


Illustrative kitchen previews, not photographs of a customer installation. Each accent colour is a separate fixed-colour product, not another mode of this strip.



**Pink**



**Blue**



**Red**



**Green**

## Compatible profiles and accessories

Select a profile with sufficient internal clearance for the 10mm PCB and its connections. Use a diffuser and mounting position suited to the cabinet design. Confirm the driver output, dimmer protocol, connector width and total load before ordering accessories.

Screens and surrounding light affect perceived colour. Use a physical sample where colour matching is critical.